

Technical data sheet

INRAL Décor Hammer paint

Weather-resistant and high-quality, this spray paint stands out thanks to the typical hammer finish effect. It can be used on a variety of materials indoors and outdoors. For revamping or repairing objects such as toolboxes, plant pots, railings and lots more.



Properties

Application:

For decorative paint coats with a hammer finish effect. For painted objects made of metal, wood, plastic, polystyrene, stone, clay, ceramics, glass as well as rattan/bast and card/paper etc

Product:

Nostalgic hammer finish effects
"Hammered" surface structure
High coverage and fast drying
Very good running properties and easy to process
Very economic
Weatherproof, for indoors and outdoors
Ideal for letterboxes, stair railings, tool boxes etc.

Binding agent base: Nitro combination resins

Spray application : For 2-3 cross coats: approx. 40-50 µm
Spray distance 15-25cm
Apply a spray mist of hammer finish paint in preferred color tone
and then a full coat with approx. 40-50 µm.

Drying times: dust-dry: after approx. 20 min.
fast-to-handling: after approx. 60 min
dry-hard: after approx. 12 hours

Recoating: with itself: at any time

Paint structure:

Metal:

1. INRAL Ground anti-corrosion paint
2. INRAL Décor Hammer paint

Wood:

1. wood primer
2. INRAL Décor Hammer paint

Plastic:

1. INRAL Plastic Ground paint
2. INRAL Décor Hammer paint

Polystyrene:

1. polystyrene primer
2. INRAL Décor Hammer paint

Note: Please check the compatibility of plastic surfaces. All other surfaces, such as e.g. stone, clay, ceramics, glass, rattan/bast, card/paper need to be primed with primer/ground. The surface to be painted must be clean, dry and free of grease. Do not spray onto synthetic resin coated surfaces because the paint may lift.

