



Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Construction chemicals
- · Application of the substance / the mixture Assembly foam
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UAB "TEGRA STATE" Kirtimų g. 67, LT-02244 Vilnius Tel./faksas +370 5 266 11 67 e-mail: info@tegra.lt

www.tegra.lt, www.tegrastate.lt

- · Further information obtainable from: info@tegra.lt
- · 1.4 Emergency telephone number: European emergency number: 112 (24h)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2	H351	Suspected of causing cancer.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.
Lact.	H362	May cause harm to breast-fed children.
Aquatic Chronic 4	H413	May cause long lasting harmful effects to aquatic life.

Additional information:

Classification of the preparation with attributed H413 phrase, taking into account the content C14-C17 chlorinated alkanes, was made on the basis of acute toxicology tests; FEICA Position Paper 17.03.2014.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 1)

· Hazard pictograms







GHS02

GHS07 GH

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomers and homologues chlorinated paraffins, C14-17

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe gas.

P263 Avoid contact during pregnancy and while nursing.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Contains fluorinated greenhouse gases covered by the Kyoto Protocol - mixture with R152a max. content 0,16 kg / 0,006 tCO2eq / GWP 33.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

GB





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		1
CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30 - 60%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33-xxxx	chlorinated paraffins, C14-17 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10); Lact., H362	< 20%
CAS: 1244733-77-4 EC number: 911-815-4 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chlorisopropyl)-phosphate • Acute Tox. 4, H302	< 20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10%
CAS: 75-37-6 EINECS: 200-866-1 Reg.nr.: 01-2119474440-43-0000	1,1-difluoroethane Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane, pure Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 10%
CAS: 6425-39-4 Reg.nr.: 01-2119969278-20-0001	2,2-dimorpholinodiethylether September 1: 2, H319	< 2%
CAS: 108-32-7 EINECS: 203-572-1 Reg.nr.: 01-2119537232-48-XXXX	propylene carbonate	< 2%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Remove uncured foam using a piece of cloth and an unagressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Fire-extinguishing powder.

CO2.

Foam.

Use fire extinguishing methods suitable to surrounding conditions.

Water spray.

- · For safety reasons unsuitable extinguishing agents: Water with full jet.
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

• Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective clothing.

Ensure adequate ventilation.

- **6.2 Environmental precautions:** Do not allow to enter sewers / surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation / exhaustion at the workplace.

Open and handle receptacle with care.

Do not pierce or burn even after use. Use only as directed on the label.

Do not mix with any other chemical products.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

(Contd. on page 5)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 4)

Observe official regulations on storing packagings with pressurised containers.

This product is subject to regulations governing the storage of highly flammable aerosol products.

Storage rooms should be equipped with heat and smoke detectors.

Electrical equipment should be explosion-proof.

Information about storage in one common storage facility:

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from reducing agents.

Store away from oxidising agents.

Store away from foodstuffs.

Store away from plastic, rubber, aluminum, light-metals.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in vertical position in closed original containers.

Protect from frost.

Store at temperature from +5°C to +30°C.

Store under lock and key and out of the reach of children.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO CAS: 115-10-6 dimethyl ether WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm CAS: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
Sen; as -NCO CAS: 115-10-6 dimethyl ether WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm CAS: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
CAS: 115-10-6 dimethyl ether WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm CAS: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm CAS: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
Long-term value: 766 mg/m³, 400 ppm CAS: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
CAS: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
Carc (if more than 0.1% of buta-1.3-diene) DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
DNELs CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Oral DNEL 20 mg/kg/day (General population, consumers)	
Oral DNEL 20 mg/kg/day (General population, consumers)	
Dermal DNEL 0.05 mg/kg/day (General population, consumers)	
Inhalative DNEL 0.05 mg/m3 (General population, consumers)	
0.05 mg/m3 (Workers)	
CAS: 85535-85-9 chlorinated paraffins, C14-17	
Oral DNEL 0.115 mg/kg/day (General population, consumers)	
Dermal DNEL 5.75 mg/kg/day (General population, consumers)	
11.5 mg/kg/day (Workers)	
Inhalative DNEL 0.4 mg/m3 (General population, consumers)	
1.6 mg/m3 (Workers)	
CAS: 108-32-7 propylene carbonate	
Dermal DNEL 10 mg/kg/day (General population, consumers)	
20 mg/kg/day (Workers)	

(Contd. on page 6)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

1.1.1.1.0	D	47.4 (0 (0))	(Contd. of pa
Inhalative	DNEL	17.4 mg/m3 (General population, consumers)	
		70.53 mg/m3 (Workers)	
		methyl ether	
Inhalative	DNEL	471 mg/m3 (General population, consumers)	
040 75 0		1,894 mg/m3 (Workers)	
		difluoroethane	
innaiative	DINEL	675 mg/m3 (General population, consumers)	
CAS: 124	4722 7	2,713 mg/m3 (Workers) -4 tris(2-chlorisopropyl)-phosphate	
Oral		0.52 mg/kg/day (General population, consumers)	
Orai	DIVLL	1.04 mg/kg/day (Workers)	
Dermal	DNFI	4 mg/kg/day (General population, consumers)	
Bonnai	DIVLE	2.08 mg/kg/day (Workers)	
Inhalative	DNEI	11.2 mg/m3 (General population, consumers)	
		5.82 mg/m3 (Workers)	
PNECs	<u> </u>	<u> </u>	
	6 97 0	liphenylmethanediisocyanate, isomers and homologues	
(freshwate		1 mg/l	
(sea water	-	0.1 mg/l	
(soil)	,	1 mg/kg	
. ,	35-85-9	chlorinated paraffins, C14-17	
(freshwate		1 mg/l	
(sea water	-	0.2 mg/l	
-	-	ents) 13 mg/kg	
(sea water			
(soil)		20 mg/kg	
CAS: 108-	-32-7 p	opylene carbonate	
(freshwate	er)	0.9 mg/l	
(sea water	-)	0.09 mg/l	
(soil)		0.81 mg/kg	
CAS: 115-	-10-6 di	methyl ether	
(freshwate	-	0.155 mg/l	
(sea water	-	0.016 mg/l	
-		ents) 0.681 mg/kg	
(sea water sediments)		,	
(soil)		0.045 mg/kg	
		difluoroethane	
(freshwate	-	0.048 mg/l (Aquatic Organisms)	
(sea water	-	0.005 mg/l (Aquatic Organisms)	
(freshwater sediments)			
(sea water sediments)			
(soil)		0.141 mg/kg (Terrestrial Organism)	
		-4 tris(2-chlorisopropyl)-phosphate	
(freshwater sediments) (sea water sediments)			
(sea water	3 C UIIII	1.7 mg/kg	
(SUII)		I.7 HIg/Ng	





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 6)

- 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

FN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Short-term exposure ≥ 10 min (EN 374)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

EN 166

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Rapidly curing foam dispensed by gaseous propellant from an

aerosol container

Colour: Different according to colouring

· **Odour:** Characteristic

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: Not applicable, as aerosol

(Contd. on page 8)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

		(Contd. of page
Flash point:	0 °C	
Auto-ignition temperature:	> +350 °C (propellant)	
Explosive properties:	Heating may cause an explosion.	
Explosion limits:		
Lower:	1.5 Vol %	
Upper:	11.0 Vol %	
Vapour pressure:	>500 kPa (in the container)	
	< 1*10-5 mmHg w 25°C (MDI)	
Density at 20 °C:	1.3 (PMDI) g/cm³	
Solubility in / Miscibility with		
water:	Insoluble	
	Reacts with water	
9.2 Other information	No further relevant information available	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Strongly reacts with water and other substances containing an active hydrogen atom.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50	LD/LC50 values relevant for classification:		
CAS: 9010	CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
Oral	LD50	>10,000 mg/kg (rat) (OECD401)	
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)	
Inhalative	LC50/4h	1.5 mg/l (ATE)	
CAS: 855	CAS: 85535-85-9 chlorinated paraffins, C14-17		
Dermal	LD50	4,000 mg/kg (rat)	
Inhalative	LC50	>3,300 mg/l (rat)	
CAS: 124	CAS: 1244733-77-4 tris(2-chlorisopropyl)-phosphate		
Oral	LD50	1,017 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
Duine em c	Drimany irritant affacts		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 9)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 8)

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

EC50 1,640 mg/l (algae)

>1,000 mg/l (daphnia) (OECD202)

>100 mg/l (Sedimentation) (OECD209)

LC50 >1,000 mg/l (fish) (OECD)

CAS: 85535-85-9 chlorinated paraffins, C14-17

EC50 >3.2 mg/l (algae) (OECD 201)

0.006 mg/l (daphnia)

LC50 >5,000 mg/l (fish)

- · 12.2 Persistence and degradability Not biodegradable.
- 12.3 Bioaccumulative potential Does not accumulate in organisms.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Do not allow to enter surface or ground water.

Dispose of in a safe manner in accordance with local / national regulations.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

Substance/mixture as a waste compound brings hazardous properties HP: 3, 4, 5, 6, 7, 13, 14

(Contd. on page 10)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 9)

European waste catalogue

15 01 11* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950
- 14.2 UN proper shipping name
- · ADR, IMDG, IATA **AEROSOLS**
- 14.3 Transport hazard class(es)
- · ADR



- · Class 2 5F Gases.
- · Label 2.1
- · IMDG, IATA



- · Class 2.1
- · Label 2.1
- · 14.5 Environmental hazards:
- · Marine pollutant: No.
- · 14.6 Special precautions for user
 - Warning: Gases.
- Hazard identification number (Kemler code): -
- · EMS Number: F-D,S-U
- · 14.7 Transport in bulk according to Annex II
- of Marpol and the IBC Code Not applicable.
- · Transport/Additional information:
- · ADR
- · Remarks: Exemption from ADR provisions by LQ principal (rule

3.4)

- Inner packaging, max. 1 liter in capacity; outer packaging - max. gross weight of 30kg.
- Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film - max. gross weight of 20kg.

(Contd. on page 11)





Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 10)

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, REACH 1272/2008/CE Regulation, CLP 2015/830/UE Regulation

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 56
- Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57 None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Recommended restriction of use

The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfill safety requirements and not to guarantee its specific properties.

In cases when application conditions are not subject to manufacturer's control, the responsibility for safe product use and obeying law regulations in particular, lies on the user's side.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 1 Revision: 22.02.2018

Trade name: FOME FLEX ULTRA FAST 75L PISTOL FOAM 870 ML

(Contd. of page 11)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1

Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – inhalation – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2
Lact.: Reproductive toxicity – effects on or via lactation
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard — Category 4