



Base:
alkyd resins

Package:
400 ml

SAND EFFECT PAINT

It's a decorative spray paint that gives a very natural sandstone effect. For the surfaces of metal, wood, plastic, polystyrene, stone, clay, ceramic, glass, paper and paperboard. For indoor or outdoor applications (protect from rain and moisture).

Area of use:

for metal, wood, plastic, polystyrene, stone, clay, ceramic, glass, paper and paperboard..

Advantages:

- Fast drying
- Realistic rust effect
- Special rough coating
- Good coverage
- For indoor and outdoor use (protect from rain and moisture)
- Easy to use and apply
- Ideal for DIY enthusiasts and craftsmen

Spray passes:

1-2 cross layers, spraying distance: 30 cm.

Drying times:

- Dust free: in around 30 min.
- Touch dry: in around 60 min.
- Complete dryness: in around 24 h.

Yield:

1,25-1,5 m² (from one 400 ml. can, one layer).

Usage:

The surface must be clean, dry and grease-free. Shake the can vigorously for 1 minute. Spraying distance 30 cm. Test the paint in an inconspicuous place to check compatibility and colour tone. For best results, use INRAL GROUND (matching the colour of the effect paint) or PLASTIC PRIMER (for plastic surfaces). Then apply SAND paint in 1-2 coats (with a 10-15 min break). For long-lasting use, apply INRAL LACQUER acrylic varnish on top (after 1 hour). The paint dries completely after 24 hours. After use, turn the can upside down and spray the valve until empty (about 3 sec.).

Safety data sheet:

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

store vertically at +10 °C...+25 °C temperature and relative air humidity of max. 60%.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-8-2-020	Sand	Matte