

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022Revision date 20-Dec-2022
Revision Number 1.01**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product Name FOME FLEX ROOF&FAÇADE COLOURED

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet**Company Name**UAB TEGRA STATE,
Savanoriu ave. 178A,
LT-03154 Vilnius,
tel. +370 5 266 11 67,
info@tegragroup.eu,
www.tegrastate.eu**1.4. Emergency telephone number** 112**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & Dibutyltin dilaurate & Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

EUH210 - Safety data sheet available on request

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Diisononyl phthalate 10 - <20 %	249-079-5	28553-12-0	[I]	-	-	-	01-2119430798-28-XXXX
Titanium dioxide 1 - <3 %	(022-006-00-2) 236-675-5	13463-67-7	[C]	-	-	-	01-2119489379-17-XXXX
Trimethoxyvinylsilane 1 - <2.5 %	(014-049-00-0) 220-449-8	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215-52-XXXX
Ethanol 0.1- <1 %	(603-002-00-5) 200-578-6	64-17-5	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610-43-XXXX
Dibutyltin dilaurate 0.1 - <0.3 %	(050-030-00-3) 201-039-8	77-58-7	STOT RE 1 (H372) Eye Irrit. 2(H319) Skin Sens. 1 (H317) Muta. 2 (H341) Repr. 1B (H360FD) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) STOT SE 1 (H370)	-	-	-	01-2119496068-27-XXXX
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 0.01 - <0.1 %	915-687-0	1065336-91-5	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	1	1	01-2119491304-40-XXXX

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	(603-001-00-X) 200-659-6	1 - <2.5	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

[I] - Restricted substance per REACH Annex XVII

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Diisononyl phthalate	249-079-5	28553-12-0	-	-	-	-	-
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	-	-	-	-	-
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	-	-	-	11	-
Ethanol	(603-002-00-5) 200-578-6	64-17-5	-	-	-	-	-
Dibutyltin dilaurate	(050-030-00-3) 201-039-8	77-58-7	-	-	-	-	-
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and water.
Ingestion	Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
 Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	Ireland	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Diisononyl phthalate 28553-12-0	-	TWA: 5 mg/m ³ STEL: 15 mg/m ³	TWA: 5 mg/m ³ STEL: 15 mg/m ³
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*
Ethanol 64-17-5	-	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³
Dibutyltin dilaurate 77-58-7	-	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³ Sk*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Diisononyl phthalate (28553-12-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	51.72 mg/m ³	
worker	Dermal	366 mg/kg bw/d	

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

Long term Systemic health effects			
--------------------------------------	--	--	--

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Ethanol (64-17-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	950 mg/m ³	
worker Long term Systemic health effects	Dermal	343 mg/kg bw/d	

Dibutyltin dilaurate (77-58-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	0,43 mg/kg bw/d	
Short term Systemic health effects worker	Dermal	2,05 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	0,02 mg/m ³	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects	Dermal	7,8 mg/kg bw/d	

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

Long term Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	
---	------	----------------	--

Ethanol (64-17-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	114 mg/m ³	
Consumer Long term Systemic health effects	Dermal	206 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	87 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Ethanol (64-17-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	154 mg/l
Marine water	15.4 mg/l
Sewage treatment plant	100 mg/l

Dibutyltin dilaurate (77-58-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0,463 µg/l
Freshwater sediment	0,05 mg/kg dry weight
Marine water	0,0463 µg/l
Marine sediment	0,005 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

Hand protection

Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in

FOME FLEX ROOF&FAÇADE COLOURED
 Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
 Revision Number 1.01

Skin and body protection	general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Respiratory protection	None under normal use conditions. In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	White
Odour	Characteristic.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	Not applicable
Initial boiling point and boiling range	No data available	Not applicable
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 66 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	800000 mm ² /s	
Dynamic viscosity	800000 mPa s	
Water solubility	Immiscible in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.34 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes
 Not applicable

9.2.2. Other safety characteristics
 No information available

SECTION 10: Stability and reactivity

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document
ATEmix (inhalation-vapour) 819.80 mg/l

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diisononyl phthalate	>9750 mg/kg (Rattus)	>3160 mg/Kg (Oryctolagus cuniculus)	>4.4 mg/L (Rattus) 4 h
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Ethanol	6200 - 15000 mg/kg (Rattus) OECD 401	-	=124.7 mg/L (Rattus) 4 h
Dibutyltin dilaurate	=2071 mg/Kg (Rattus) (OECD 401)	>2000 mg/kg (Rattus) (OECD 402)	-
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 = 3230 mg/Kg (Rattus) (OECD 401)	LD50 >3170 mg/Kg (Rattus) (OECD 402)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Respiratory or skin sensitisation OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Titanium dioxide (13463-67-7)

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information
 Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Dibutyltin dilaurate	Muta. 2

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Dibutyltin dilaurate	Repr. 1B

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Diisononyl phthalate 28553-12-0	EC50: >500mg/L (72h, <i>Desmodesmus subspicatus</i>) EC50: >1.8mg/L (96h, <i>Pseudokirchneriella subcapitata</i>)	LC50 96 h > 100 mg/L (<i>Brachydanio rerio</i> semi-static)	-	EC50: >500mg/L (48h, <i>Daphnia magna</i>) EC50: >0.06mg/L (48h, <i>Daphnia magna</i>)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (<i>Cyprinodon variegatus</i>) OECD 203	-	-	-		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (<i>Desmodesmus subspicatus</i>) EU Method C.3	LC50 (96h) = 191 mg/l (<i>Oncorhynchus mykiss</i>)	-	EC50(48hr) 168.7mg/l (<i>Daphnia magna</i>)		
Ethanol 64-17-5	EC50 72hr 12.9 g/l (<i>Selenastrum capricornutum</i>) NOEC 3.24 g/l (<i>Skeletonema costatum</i>)	LC50: >100mg/L (96h, <i>Pimephales promelas</i>)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50: (48h, <i>Daphnia magna</i>) EC50: =12.34 mg/L		
Dibutyltin dilaurate 77-58-7	EC50 (72h) >= 1 mg/l (<i>Desmodesmus subspicatus</i>)	LC50 (96h) = 3.1 mg/l (<i>Danio rerio</i>)	-	EC50 (48h) = 0.463 mg/l (<i>Daphnia magna</i>)		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	-	LC50 (96h) = 0.9 mg/L	-	-	1	1

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Diisononyl phthalate	9.7
Trimethoxyvinylsilane	1.1
Ethanol	-0.35
Dibutyltin dilaurate	4.44
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	2.77

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Diisononyl phthalate	The substance is not PBT / vPvB PBT assessment does not apply
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Ethanol	The substance is not PBT / vPvB PBT assessment does not apply
Dibutyltin dilaurate	The substance is not PBT / vPvB
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Waste codes / waste designations according to EWC Waste codes should be assigned by the user based on the application for which the product was used.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

FOME FLEX ROOF&FAÇADE COLOURED
 Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
 Revision Number 1.01

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diisononyl phthalate	28553-12-0	52[a].
Dibutyltin dilaurate	77-58-7	30. 75. 20.

52 . Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Dibutyltin dilaurate	I.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009
 Not applicable

Persistent Organic Pollutants
 Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H332 - Harmful if inhaled
 H341 - Suspected of causing genetic defects
 H360FD - May damage fertility. May damage the unborn child
 H361f - Suspected of damaging fertility
 H370 - Causes damage to organs
 H372 - Causes damage to organs through prolonged or repeated exposure
 H400 - Very toxic to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

SVHC: Substances of Very High Concern for Authorisation:
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
 STOT RE: Specific target organ toxicity - Repeated exposure
 STOT SE: Specific target organ toxicity - Single exposure
 EWC: European Waste Catalogue
 LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IATA: International Air Transport Association

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
 IMDG: International Maritime Dangerous Goods
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
 European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
 European Chemicals Agency (ECHA) (ECHA_API)
 EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AEGl(s))
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 NIOSH (National Institute for Occupational Safety and Health)
 Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
 Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By	Product Safety & Regulatory Affairs
Revision date	20-Dec-2022
Revision note	SDS sections updated 2
Training Advice	No information available
Further information	No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

FOME FLEX ROOF&FAÇADE COLOURED
Supersedes Date: 25-Apr-2022

Revision date 20-Dec-2022
Revision Number 1.01

End of Safety Data Sheet