

DECLARATION OF PERFORMANCE

No.: TEG-1 4778967

I. Unique identification code of the product type:

FOMEFLEX SILICONE N

Reviewed: 01 09/04/2025_LT

In accordance with CPR, Regulation (EU) No 305/2011

2. Intended use(s):

- Sealant for façade interior and exterior works, intended for use in cold weather conditions.
- Sealant for sealing and glazing, intended for use in cold weather conditions.
- Sealant for pedestrian walkways for indoor works.

3. Manufacturer:

Manufacturer's name and contact address, as required under Article 11(5):

UAB TEGRA STATE

Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA

Tel.:+37052661167

www.tegrastate.eu

E-mail: info@tegragroup.eu

4. System(s) for assessment and verification of constancy of performance:

- System 3
- System 3: reaction to fire

5. Harmonised standard:

- EN 15651-1:2012: Type F: EXT-INT-CC; 25LM
- EN 15651-2:2012: Type G-CC; 25LM
- EN 15651-i.j:2012: Type PW: INT; 25LM

6. Notified body (bodies):

ZAG, NB 1404 carried out the determination of the product type according to System 3.

7. Declared performance(s)	Performance	Harmonised technical specification	
TYPE F: EXT-INT			
Reaction to fire	Class E	EN 15651-1	
Release of dangerous substances into the environment	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume (shrinkage):	≤ 10 %		
Adhesion / cohesion after immersion in water	NF		
Elastic recovery	≥70 %		
Tensile properties at 23°C	≤ 0.4 MPa		
Tensile properties at -20°C	≤ 0.6 MPa		
Tensile properties maintained under extension	NF		
Adhesion / cohesion under variable temperature	NF		
Durability	Passed		
TYPE F: EXT-INT-CC			
Tensile properties, modulus at break	≤ 0.9 MPa		
Tensile properties maintained under extension	NF		
TYPE G			
Reaction to fire	Class E	EN 15651-2	
Release of dangerous substances into the environment	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume (shrinkage):	≤ 10 %		
Elastic recovery	≥ 60%		
Tensile properties at 23°C	≤ 0.4 MPa		
Tensile properties at -20°C	≤ 0.6 MPa		
Tensile properties maintained under extension	NF		
Adhesion / cohesion under variable temperature	NF		
Adhesion / cohesion maintained under extension after immersion in water	NF		
Adhesion / cohesion after exposure to heat, water, and artificial light	NF		
Resistance to compression	0,37 MPa		
Durability	Passed		
TYPE G-CC			
Tensile properties, modulus at break	≤ 0.9 MPa	EN 15651-2	
Tensile properties maintained under extension	NF		

TYPEPW: INT		EN 15651-4
Reaction to fire	Class E	
Release of dangerous substances into the environment	NPD	
Resistance to flow	≤ 3 mm	
Loss of volume (shrinkage):	≤ 10 %	
Elastic recovery	≥ 60%	
Tensile properties at 23°C	≤ 0.4 MPa	
Tensile properties at -20°C	≤ 0.6 MPa	
Tensile properties maintained under extension	NF	
Adhesion / cohesion under variable temperature	NF	
Adhesion / cohesion maintained under extension after immersion in water	NF	
Resistance to tearing	NF	
Durability	Passed	

Conditioning: Method A

Substrate: glass, aluminium, mortar + primer

„The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.”

Signed on behalf of the manufacturer:

Daniel Počikovskij
Product Group Manager

Vilnius 09/04/2025

(parašas)

