

DECLARATION OF PERFORMANCE

Nr. 2025-05-20

1. Unique identification code of the product-type:

Fome Flex silacryl

2. Type, batch or serial number or any other element allowing identification of the construction product:

The batch number is indicated on the packaging.

3. Intended use or uses of the construction product, in accordance with the applicable technical specification, as foreseen by the manufacturer:

Sealant for joints in sanitary premises of buildings exposed to non-pressurised water

4. Name, registered trade name or registered trade mark and contact address of the manufacturer, factory address:

UAB TEGRA STATE

Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA

Tel.:+37052661167

www.tegrastate.eu

E-mail: info@tegragroup.eu

5. Where applicable, name and address of the authorised representative with the powers set out in Article 18(15) of the Law on Construction of the Republic of Lithuania:

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Chapter V of this Regulation:

System 4 (thermal conductivity, sound absorption index) and system 3

7. Name of the certification body or testing laboratory:

Notified body Tecnalía, identification number 1292

8. Declared performance:

EN 15651-3:2012 Typo S

Effect: Method A

Substrate: Anodized aluminum with Primer 203

| Essential characteristics | Performance characteristics | Testing standard | Harmonized technical specification |
|--|-------------------------------|----------------------|------------------------------------|
| reaction to fire | Class F | EN 13501-1:2007+A1 | EN 15651-3:2012 |
| release of chemicals hazardous to the environment and health | see product safety data sheet | EN 15651-1:2012; 4.5 | EN 15651-3:2012 |
| Water and air tightness due to: | | | |
| resistance to leakage | ≤ 3 mm | modified EN ISO 7390 | EN 15651-3:2012 |
| volume loss | ≤ 55 % | EN ISO 10563 | EN 15651-3:2012 |

| | | | |
|---|--------|------------------------------|-----------------|
| Tensile properties: (i.e. elongation): - after immersion in water (23 °C) | ≥ 25 % | EN ISO 10591 | EN 15651-3:2012 |
| Tensile properties: (i.e. elongation): - under sustained tension after immersion in water | NPD | EN ISO 10590 | EN 15651-3:2012 |
| growth rate of microorganisms | 2 | EN ISO 846:1997, procedure B | EN 15651-3:2012 |
| durability | passed | EN ISO 846, EN ISO 10591 | EN 15651-3:2012 |

(*) See product safety data sheet
NPD: No Performance Determined

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

10. Signed (For and on behalf of the Manufacturer):

Vilnius 2025.05.20



(signature)



*Eksplotacinių savybių deklaracija parengta pagal „STATYBOS TECHNINĮ REGLAMENTĄ STR 1.01.04:2015“