

DECLARATION OF PERFORMANCE



Page: 1

according Annex III of the Regulation (EU) No 305/2011 TEG0310100
Edition: 28.03.2024

1. Unique identification code of the product-type:

POINT 120 Clear Power

POINT

2. **Type, batch or serial number** or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. **Intended use or uses** of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 15651-1:2012 Type F-EXT-INT Class 12,5P

non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face.

EN 15651-3:2012 Type S Class S 1

sealant used for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water

4. Name, registered trade name or registered trade mark and contact address of the **manufacturer** as required pursuant to Article 11(5):

UAB TEGRA STATE, Savanorių pr. 178A, LT-03154 Vilnius, LITHUANIA

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. **System or systems of assessment** and verification of constancy of performance of the construction product as set out in Annex V:

system 3 for type of testing
system 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a **harmonised standard**:

The notified body Tecnalía, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

The notified body Tecnalía, identification number 1292, performed the determination of the product-type on the basis of type testing under system 3 and issued: a test report

8. In case of the declaration of performance concerning a construction product for which a **European Technical Assessment** has been issued:

not relevant

9. Declared performance

EN 15651-1:2012 Type F-EXT-INT

Conditioning: Method A

Substrate: anodised aluminium without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-1:2012

DECLARATION OF PERFORMANCE



Page: 2

according Annex III of the Regulation (EU) No 305/2011 TEG0310100
Edition: 28.03.2024

Water tightness and air tightness:			
Resistance to flow	≤ 3mm	modified EN ISO 7390	EN 15651-1:2012
Loss of volume	≤ 25%	EN ISO 10563	EN 15651-1:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 100%	EN ISO 8339	EN 15651-1:2012
Tensile properties (i.e. elongation): -at maintained extension after water immersion	NPD		EN 15651-1:2012
Tensile properties (i.e. secant modulus): -for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	NPD	modified EN ISO 8339	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): -for non-structural sealants used in joints in cold climate areas (-30°C)	NPD	modified EN ISO 8340	EN 15651-1:2012
Durability	Pass	modified EN ISO 7390; EN ISO 10563; EN ISO 8339;	EN 15651-1:2012

EN 15651-3:2012 Type S

Conditioning: Method A

Substrate: anodised aluminium without primer

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	See product safety data sheet	EN 15651-1:2012; 4.5	EN 15651-3:2012
Water tightness and air tightness:			
Resistance to flow	≤ 3mm	modified EN ISO 7390	EN 15651-3:2012
Loss of volume	≤ 20%	EN ISO 10563	EN 15651-3:2012
Tensile properties (i.e. elongation): - after immersion in water at (23 °C)	≥ 25%	EN ISO 10591	EN 15651-3:2012
Tensile properties (i.e. elongation): - at maintained extension after water immersion	NPD	EN ISO 10590	EN 15651-3:2012
Microbiological growth	0	EN ISO 846:1997, procedure B	EN 15651-3:2012
Durability	Pass	modified EN ISO 7390; EN ISO 10563; EN ISO 10591; EN ISO 10590; EN ISO 846:1997,	EN 15651-3:2012

UAB TEGRA STATE

Savanorių pr. 178A, LT-03154 Vilnius, LITHUANIA

Tel. +370 5 266 11 67

DECLARATION OF PERFORMANCE



Page: 3

according Annex III of the Regulation (EU) No 305/2011 TEG0310100
Edition: 28.03.2024

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the
manufacturer by:

Daniel Pockovskij
(Product Manager)



28.03.2024, Vilnius

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance

UAB TEGRA STATE
Savanorių pr. 178A, LT-03154 Vilnius, LITHUANIA
Tel. +370 5 266 11 67