

REINFORCED TAPE FOR PLASTERING WORKS, ZOOM



DESCRIPTION:

General purpose reinforced tape with high adhesive strength designed for use in plastering applications. Reinforced plastering tape made of synthetic rubber with an elastic, easy-to-stick adhesive and a waterproof PE-coated fabric that can be torn off by hand.

USE:

ZOOM reinforced plastering tape is suitable for use on smooth or uneven surfaces such as stainless steel, polyethylene, glass and wood. It is used for general purposes such as repairing, sealing, protecting or sealing joints against leakage of unnecessary materials.

TECHNICAL DATA:

Support material	PE(polyethylene) coated fabric
Glue	Hotmelt/synthetic rubber
Thickness [μm]	170
Mesh density (fabric)	32
Adhesion to metal [N/25mm]	20
Rolling ball stickiness [cm]	< 1
Tensile strength [N/25 mm]	75
Temperature resistance [°C]	-10 to +75

SIZES:

WIDTH [mm]	19, 30, 38, 48
LENGTH [m]	33
INTERNAL [mm]	76

STORAGE CONDITIONS:

Store in a cool, dry place away from direct sunlight and heat sources. If the product storage requirements are followed, the product has a shelf life of 12 months.

NOTES:

All statements, technical information and product recommendations are based on tests in our laboratories which we believe to be reliable. However, in all cases the user should determine the suitability of the product for the intended use and the user assumes all risk and liability in this regard. Neither the seller nor the manufacturer shall be liable for any direct, incidental or consequential loss or damage arising from the use of the product. Details of test methods are available upon request.