

PROFESSIONAL PAINT TAPE SENSITIVE PLUS



Description:

Professional painting tape Sensitive Plus, made of Japanese rice paper - Washi. Specially designed for particularly sensitive indoor surfaces, such as plaster or newly painted surfaces.

Usage:

The tape is suitable for painting on extremely sensitive and delicate surfaces for long periods of time. Depending on the type of surface, removability can be guaranteed for up to 14 days. The tape is resistant to high temperatures up to +90 °C for 1 hour and has excellent UV resistance up to 14 days, depending on the application conditions.

Technical specification:

Basis	Washi paper
Color	Violet
Glue	Acrylic

	Unit of measure	Data	Norm
Width	[mm]	25, 30, 38, 48	-
Middle diameter	[mm]	76	-
Tape thickness	[μm]	83	EN 1942
Elongation during stretching	[%]	4	-
Tensile strength	[N/mm ²]	41	-
Adhesion to steel	[N/10 mm]	0,9	EN 1939
Rupture	[h]	≥4	EN 1943
Operating temperature	[°C]	< 90 °C	-

Sizes:

Width [mm]	25; 30; 38; 48;
Length [m]	50

STORAGE CONDITIONS:

Store in a cool, dry place away from direct sunlight and heat sources. If the product storage requirements are followed, the product has a shelf life of 12 months.

NOTES:

All statements, technical information and product recommendations are based on tests in our laboratories which we believe to be reliable. However, in all cases the user should determine the suitability of the product for the intended use and the user assumes all risk and liability in this regard. Neither the seller nor the manufacturer shall be liable for any direct, incidental or consequential loss or damage arising from the use of the product. Details of test methods are available upon request.