

## DOUBLE-SIDED POLYPROPYLENE TAPE



### Description:

Double-sided tape with synthetic rubber adhesive, polypropylene material and brown siliconized paper film. The tape has good initial adhesion and adheres well to smooth surfaces.

### Usage:

For long-term fastening of carpets, rugs, skirting boards, profiles, ceiling strips and decorative film.

### Characteristics:

Basis	Polypropylene
Paper	Siliconized paper 70 µm
Glue	Synthetic rubber
Total thickness without paper [µm]	75
Adhesion to metal RT [N/25 mm]	14
Rolling resistance RT [cm]	< 10
Slip resistance RT [hours]	> 168
Temperature resistance [°C]	from -10 to +75

### Sizes:

Width [mm]	48
Length [m]	5, 10, 25
Inside [mm]	3"

### Storage/transportation conditions:

Store in a cool, dry place, away from sunlight and direct heat sources. If storage conditions are met, the product is guaranteed for 12 months.

**Additional information:**

All statements, technical information and product recommendations are based on tests in our laboratories which we believe to be reliable. However, in all cases the user should determine the suitability of the product for the intended use and the user assumes all risk and liability in this regard. Neither the seller nor the manufacturer shall be liable for any direct, incidental or consequential loss or damage arising from the use of the product. Details of test methods are available upon request.