

REINFORCED TAPE, GREY



Description:

Ready-to-use reinforced tape. Reinforced tape based on synthetic rubber with a waterproof PE-coated fabric that can be torn off by hand. The reinforced tape has a strong initial adhesion and good bonding strength.

Usage:

Reinforced tape is ideal for bonding smooth and rough surfaces such as stainless steel, polyethylene, glass and wood. It is used for general applications such as repair, sealing, protection and bonding.

Technical data:

Base type	PE coated mesh
Glue	Hotmelt/synthetic rubber
Total thickness [μm]	150
Material density (mesh) [kg/m ³]	18
Adhesion to steel [N/25 mm]	17.5
Rolling resistance [cm]	< 3
Tensile strength [N/25 mm]	70
Temperature resistance [°C]	-10 to +75

Sizes:

Width [mm]	48
Length [m]	5, 10, 25, 50
Inside [mm]	76

Storage/transportation conditions:

Store in a cool, dry place, away from sunlight and direct heat sources. If storage conditions are met, the product is guaranteed for 12 months.

Additional information:

All statements, technical information and product recommendations are based on tests in our laboratories which we believe to be reliable. However, in all cases the user should determine the suitability of the product for the intended use and the user assumes all risk and liability in this regard. Neither the seller nor the manufacturer shall be liable for any direct, incidental or consequential loss or damage arising from the use of the product. Details of test methods are available upon request.