

POLYETHYLENE COVER WITH MASKING TAPE



Description

Statically charged pre-folded HDPE film with pre-applied crepe masking tape. The product is supplied in shrink-wrapped packs.

Usage

This time-saving, compact 2-in-1 masking concept can be used to temporarily protect doors, windows, window sills, radiators and furniture during painting and plastering. Residue-free tape after removal. The polyethylene cover is available in various sizes, making it suitable for small and large surfaces.

Characteristics

Adhesive tape	
Backing	Smooth crepe
Adhesive	Natural rubber
Total thickness [µm]	125
Clean removal	2 days
Adhesion to steel RT [N/25mm]	6.5
Tensile strength, MD [N/25 mm]	87
Elongation at break, MD [%]	9
Film	
Film material	HDPE
Colour	Transparent, milky-white
Electrostatically charged	Yes
Thickness [µm]	8

Sizes

Unfolded width x roll length:

550 mm x 20 m

1400 mm x 20 m

2100 mm x 20 m

2700 mm x 20 m

Storage/Transport Conditions

Store in a cool, dry place away from sunlight and direct heat sources. If storage conditions are observed, the product is guaranteed for 12 months.

Additional Information

All statements, technical information and product recommendations are based on tests carried out in our laboratories which we believe to be reliable. However, in all cases the user should determine the product's suitability for the intended use, and the user assumes all associated risk and responsibility. Neither the seller nor the manufacturer is liable for any loss or damage, incidental or consequential, arising from the use of the product. Detailed information on test methods is available upon request.