

Protective film + Precision tape



Description

This time saving and compact 2-in-1 masking concept can be used for temporary protection of doors, windows, windowsills, radiators and furniture during painting and plastering. It can be supplied in many unfold dimensions and is therefore suitable for small and large surfaces. The tape is suitable for masking on fragile and delicate surfaces during extended periods of time. Depending on the type of surface the removability can be guaranteed up to 6 months.

Advantages

- A statically charged prefolded HDPE film with a yellow impregnated paper tape.
- The product is individually shrink-wrapped.
- It is intended for long term use thanks to its special high performance acrylic adhesive.
- The product has a strong but thin carrier which provides extra strength to the product and allows very sharp paintlines at the same time.

Features

| | |
|-----------------------|-----|
| Initial adhesion/tack | ••• |
| Final adhesion | ••• |
| Dimensional stability | ••• |

Suitability on

| | |
|---|-----|
| High energy plastics: PVC, PC, ABS, ... | ••• |
| Low energy plastics: PE, PP, ... | ••• |
| Metal | ••• |
| Paper/Cardboard | ••• |

••• very good •• good • limited

Technical data

| Technical data | Test | Value |
|------------------------|------------|------------|
| Tape | | |
| Peel adhesion to SS | Afera 5001 | 3,5 N/25mm |
| Tensile Strength | Afera 5004 | 75 N/25mm |
| Elongation | Afera 5004 | 5% |
| Temperature resistance | | +90 °C |

Storage conditions

Store in a cool dry place away from sunlight and direct heat sources.

Storage temperature: 23 °C ± 2 °C

Relative humidity: 50% RH ± 5%

As far as the storage conditions are respected, the product is guaranteed 12 months.

Available sizes:

550 mm x 20 m

1400 mm x 20 m

2100 mm x 20 m

2700 mm x 20 m