



Base:
vinyl

Package:
400 ml

Inral ALU ZINC spray paint

Aluminum effect and anticorrosion – protective, decorative and restorative spray coat for steel, cast iron, galvanized and ZINC GROUT anticorrosive surfaces.

Area of use:

Used in construction for galvanized surfaces such as roofs, gutters, window sills, fences, etc. Also used in heavy industry in the manufacture of pipes and other equipment. Can be used at home to paint racks, caravans, wheelbarrows, bicycles and many other items.

Advantages:

- Fast-drying with perfect coating and adhesive properties for galvanised steel bases
- Resilient to effects of industrial, urban and rural environments
- The appearance of the coat is close to galvanized or aluminium surfaces
- Resilient to temperatures from -20 to 60 (periodically to 80)°C
- Lead- and chromates-free
- Ozone-friendly oxes etc.

Spray passes:

1-2 cross layer, spraying distance: 30 cm.

Drying times:

- Touch dry: about 20 min.
- Other layers: after 60 min.
- Other products: after 3h

Yield:

2 m² (from one 400 ml. can, one layer).

Usage:

Clean and degrease the surface. Shake the can vigorously for 1 min. Spray evenly on the surface at a distance of 30 cm. Most effective when applied as a thin coat, with breaks, in several layers. When finished, turn the can upside down and clean the pulveriser by holding it down for a few seconds.

Safety data sheet:

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-7-3-001	Aluminium	Matte