

## PROFESSIONAL PAINTING TAPE ZOOM Ultra Sensitive



### Description:

„ZOOM Ultra Sensitive“ Painters Tape designed to ensure professional finish even on the most sensitive surfaces, where any other product would cause damage. Resistant to moisture and most common water and solvent base paints. Ensures clean and gentle removal up to 1 week after application on extremely delicate surfaces (wallpapers, fresh paints). Clean removal up to 2 weeks on common indoor surfaces (PVC, Glass, Wood, Aluminium).

### Advantages:

- Suitable for use on the most sensitive surfaces
- Leaves no adhesive residue
- Produces a crisp paint line
- Prevents paint bleed-through
- Extremely thin tape leaves no paint ridge when painted over

### Applicable surfaces:

- PVC
- Glass, windows, mirrors
- Treated, painted or untreated wood
- Aluminium and other smooth architectural materials
- Freshly painted surface (dry enough to touch)
- Wallpapers and delicate, textured wall coverings
- Primed drywall and plasterboard
- Delicate cabinetry, veneers and laminates
- Finished hardwood floors and delicate tiles

### Areas of application:

For indoor painting jobs, requiring fast and high quality results.

**Technical data:**

<b>Base</b>	WASHI paper
<b>Colour</b>	Pink
<b>Adhesive</b>	Water based acrylic
<b>Thickness [µm]</b>	75
<b>Adhesion to Steel [N/cm]</b>	0.45
<b>MD Tensile strength [N/cm]</b>	30
<b>MD Elogation at break [%]</b>	3.5
<b>Temperature resistance</b>	90°C (up to 60 minutes)
<b>UV Resistance</b>	Up to 7 days (indoors)
<b>Clean removal</b>	Up to 14 days (indoors)

**Sizes:**

Width [mm]      30; 38; 48  
 Length [m]      50

**Instructions of use:**

**Preparation:** Store the tape for 24 hours at room temperature (>18°C) before use. Ensure the target surface is free of excessive dust or debris.

**Application:** Apply the tape evenly with light pressure to secure the edge and prevent paint bleeding.

**Removal:** The tape guarantees clean and gentle removal. The tape can be mounted for up to 14 days indoors on very sensitive surfaces without leaving adhesive residue or damaging the substrate.

**STORAGE CONDITIONS:**

Store for 24 hours at room temperature >18°C, before use. Store in a cool dry place away from sunlight and direct heat sources. As far as the storage conditions are respected, the product is guaranteed 12 months.

**NOTES:**

All statements, technical information and product recommendations are based on tests in our laboratories which we believe to be reliable. However, in all cases the user should determine the suitability of the product for the intended use and the user assumes all risk and liability in this regard. Neither the seller nor the manufacturer shall be liable for any direct, incidental or consequential loss or damage arising from the use of the product. Details of test methods are available upon request.