

INRAL ALU PRIMER

Protective primer with high adhesion to aluminium and light alloys. Can also be used on iron and steel. Quick drying. It can be sanded and repainted with acrylic, nitro and synthetic enamels. Perfectly suited for use in industry, crafting, DIY and bodywork.



Base:
Nitro-synthetic

Package:
400 ml

Area of use:

Excellent adhesion on aluminum and light alloys. Can also be used on iron and steel. Incompatibility: do not apply on surfaces with residues of products containing silicones.

Advantages:

- High coverage
- Fast drying
- For indoor and outdoor use
- Good adhesion to aluminum and light alloys

Spray passes:

1-2 cross layer, spraying distance: 20-25 cm.

Drying times:

- Dust free: 5 - 10 min.
- Touch dry: 20 min.
- Completely dry: 24 h.

Gloss level:

Matt: <15 gloss at 60°

Yield:

1,5 - 2 m² (from one 400 ml. can, one layer).

Usage:

Use between 10 and 25 °C on surfaces at the same temperature, in well ventilated environments. Mask the parts not to be treated. The painted surface must be clean, dry and grease-free. Shake the can vigorously for approx. 2 minutes. Make a spray test on a separate surface. Spray a layer in cross passes, from a distance of 20-25 cm. If necessary repeat the application after a few minutes. After use, turn the can upside down and spray the valve for few seconds for cleaning.

TECHNICAL DATA SHEET

INRAL²

Safety data sheet:

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

Store upright in a dry place at +10°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-7-2-015	Grey	Matt