

INRAL WALL STAIN BLOCKER

Acrylic white opaque spray paint. It covers and blocks stains on walls from penetrating the surface before painting with wall or other types of paint. The product reduces the number of necessary layers of wall paint and painting time. Easy to apply, dries quickly.

Area of use:

Excellent adhesion to walls, cement, plasterboard. Suitable for covering mould, soot, moisture, grease, dirt, pen, pencil, graffiti, nicotine and various other stains.

Advantages:

- White ultra-opaque
- Covers and shields stains
- High coverage
- Fast drying
- Reduces the number of coats needed
- Reduces painting time

Spray passes:

1-3 cross layer, spraying distance: 20-25 cm.

Drying times:

- Dust free: 5 - 10 min.
- Touch dry: 15 - 20 min.
- Completely dry: 16 - 20 h.

Gloss level:

Matt: <10 gloss at 60°

Yield:

1,5 - 2 m² (from one 400 ml. can, one layer).

Usage:

Use between 10 and 25 °C on surfaces at the same temperature, in well ventilated environments. Mask the parts not to be treated. The painted surface must be clean, dry and grease-free. Shake the can vigorously for approx. 2 minutes. Make a spray test on a separate surface. Spray a layer in cross passes, from a distance of 20-25 cm. If necessary repeat the application after a few minutes. After use, turn the can upside down and spray the valve for few seconds for cleaning.



Base:
Modified acrylic

Package:
400 ml

TECHNICAL DATA SHEET

INRAL²

Safety data sheet:

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

Store upright in a dry place at +10°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-7-4-015	White	Matt